


Broadband, Convoluted, Open-Cell, Foam Absorber



BROADBAND CONVOLUTED OPEN-CELL FOAM ABSORBER

Eccosorb OCF is a series of premium-grade tapered broadband absorbers. It has a convoluted shape similar to the Eccosorb CV material, but is made from a much more open-cell foam material. This open structure allows the piece to be used at high humidity although long term exposure to water and UV should be avoided. For indoor higher power requirements, cooling air can be circulated through the foam structure, either by natural convection or by fan, to keep the temperature of the piece down. Because of the rounded convolutions and lack of sharp corners and tips, Eccosorb OCF is the preferred absorber for mm wave frequencies and for grazing incidence angles out to 60° off-normal.

FEATURES AND BENEFITS

- Open-cell
- Broadband absorption due to high thickness
- High reflectivity due to geometric structure

MARKETS

- Commercial Telecom
- Test and Measurement

SPECIFICATIONS

TYPICAL PROPERTIES	ECCOSORB OCF
Frequency Range	>1.5 GHz
Max. Service Temperature °C (°F)	90 (194)
Power handling with unimpeded airflow	8 kW/m ²

Data for design engineer guidance only. Observed performance varies in application. Engineers are reminded to test the material in application.

APPLICATIONS

- Absorbing collars (shrouds) around the edges of high performance antennas
- MM-wave applications
- Small test boxes

AVAILABILITY

- Eccosorb OCF is available in standard piece sizes of 61 cm x 61 cm.
- Three grades are available, Eccosorb OCF-3, OCF-4 and OCF-6, with resp. heights of 7.5 cm, 10 cm and 15 cm. The thickness (height) determines primarily the low frequency end of performance, all grades have similar performance at millimeter wave frequencies.
- Eccosorb OCF is supplied with the front surface painted white.
- If the primary application is for millimeter wave frequencies, it is recommended to ask for absorber to be supplied without paint, as it can have a negative effect on the reflectivity performance.

GRADE	LOW FREQUENCY LIMIT (IN GHz) OF INDICATED REFLECTIVITY			
	-20 dB	-30 dB	-40 dB	-50 dB
OCF-3	3	6	9	25
OCF-4	2.5	5	8	25
OCF-6	1.5	3	6	25

The table gives the specified reflectivity values, showing the frequency at which a particular reflectivity can be expected for each grade. Just as with Eccosorb CV, a reflectivity of -40 dB can be expected at 94 GHz. There is little degradation of the reflectivity for incidence angles as wide as 60° off-normal incidence.

INSTRUCTIONS FOR USE

- Eccosorb OCF can be bonded to structures using a contact adhesive such as the Eccostock[®] foam adhesive. In this case, several coatings of the adhesive should be applied to the back surface of the absorber and allowed to dry, to create a solid back surface.
- It is preferred to use mechanical means to supplement the adhesive, impaling the piece on plastic pins or hooks which is particularly effective.
- The curved absorber tips should be pointed in the direction of the transmitting signal.

RFP-DS-OCF 113015

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.